

GENERAL FEATURES

- 30W / 50W (136-174 MHz) Models
- 30W / 45W (400-470, 450-520 MHz) Models
- 512 CH-GID / 128 Zones
- Dash & Remote Mount
- Dual Control Head Remote Mount
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- Function/Status LCD Icons
- Multi-Language Display
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Power Control
- 4 Up/Down Selectors
- 6 Front PF Keys
- Emergency/AUX Key
- 4W Speaker Audio
- DB-25 Accessory Connector
- 9 Programmable AUX I/Os
- 2 Programmable AUX Outputs
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP-54/55 Water & Dust Intrusion
- PC Serial Interface
- SDM Manual Input¹
- Transparent Data Mode¹
- GPS Receiver Option
- VGS-1 Voice Guide / Voice & GPS Data Storage Option

DIGITAL – COMMON

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging¹
- Remote Stun/Kill¹

DIGITAL – COMMON (Cont)

- Remote Check¹
- Short & Long Data Messages¹
- GPS Location with Voice¹
- NXDN® Scrambler Included
- DES Encryption Module Option
- AES & DES Encryption Module Option
- AES/DES Software Key Loader Option

DIGITAL CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation
- Conventional IP Networks
- Site Roaming

DIGITAL TRUNKING MODE

- Individual Private Call
- Group Call & Broadcast Call
- Transmission Trunked Mode²
- Message Trunked Mode²
- Call Queuing with Priority²
- Late Entry (UID & GID)²
- 4 Priority Monitor ID's²
- Remote Group Add¹
- Failsoft Mode

MULTI-SITE IP NETWORKS COMPATIBLE

- Individual Private Call
- Group Call & Broadcast Call
- Transmission Trunked Mode²

MULTI-SYSTEM COMPATIBLE

- 8 Trunked Networks³
- UID Lists for each network

SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)

ANALOG MODE - GENERAL

- 25 & 12.5 kHz Channels
- Conventional & LTR® or MPT Zones
- FleetSync®/II, MDC-1200, DTMF
- QT / DQT & Two-Tone (Conventional Zones Only)
- Voice Inversion Scrambler (16 Codes)

MPT ZONES*

- Single-Site Trunking
- Multi-Site Network Trunking
- 8 Network Capacity
- Network Roaming / Registration

FleetSync®II (FM)

- PTT ID ANI / Caller ID
- Selective / Group Call
- Emergency, Status & Text Messages¹

MDC-1200

- PTT ID ANI / Caller ID
- Emergency, Radio Check & Inhibit

* Optional feature



Options

<ul style="list-style-type: none"> KMC-35 Microphone KMC-36 Microphone with Keypad KMC-9C Control Station Desktop Microphone KES-5 External Speaker 	<ul style="list-style-type: none"> VGS-1 Voice Guide & Storage Unit KRK-10 Panel Remote Kit KRK-13 Dual Control Head Remote Kit KPS-15 DC Power Supply 	<ul style="list-style-type: none"> KAP-2 Horn Alert / PA Relay Unit KCT-23M DC Cable (10 feet) KCT-23M3 DC Cable (23 feet) 	<ul style="list-style-type: none"> KCT-46 Ignition Sense Cable KMB-10 Key Lock Adapter KLF-2 Line Noise Filter
---	--	--	--

Main Specifications

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

GENERAL		NX-700(H) K	NX-800(H) K
Frequency Range	Type 1 Type 2	136-174 MHz	450-520 MHz 400-470 MHz
Number of Channels		512	
Zones		128	
Max. Channels per Zone		250	
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
Operating Voltage		13.6 V DC ± 15%	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		± 1.0 ppm	
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included	6.30 x 1.77 x 6.18 in (160 x 45 x 157 mm)	
Weight (net)		3.04 lb (1.38 kg)	
FCC ID	K Type 1 K Type 2 HK Type 1 HK Type 2	kDDCHIF9B((((kDDCHIF9B((((kDDCHIF9B((((kDDCHIF9B((((kDDCHIH9D((((kDDCHIH9E kDDCHIH9D kDDCHIH9E
IC Certification	K Type 1 K Type 2 HK Type 1 HK Type 2	282F-378602 282F-378602	282F-378704 BIBe6CHIH9E(((282F-378704 BIBe6CHIH9E

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Specifications are subject to change without notice, due to advancements in technology.

FleetSync® is a registered trademark of JVCKENWOOD Corporation.
LTR® is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
Windows® is a registered trademark of Microsoft Corporation.
NXDN® is a trademark of JVCKENWOOD Corporation and Icom Inc.
NEXEDGE® is a trademark of JVCKENWOOD Corporation.

RECEIVER		NX-700(H) K	NX-800(H) K
Sensitivity	Digital @ 6.25 kHz (3% BER) Digital @ 12.5 kHz (3% BER) Analog (12 dB SINAD)	0.20 μV 0.28 μV 0.25 μV	0.20 μV 0.25 μV 0.25 μV
Selectivity	Analog @ 25 kHz Analog @ 12.5 kHz	80 dB 70 dB	80 dB 70 dB
Intermodulation	Analog	75 dB (±50,100 kHz)	
Spurious Response	Analog	90 dB	85 dB
Audio Distortion		Less than 3%	
Audio Output		4 W / 4 Ω	
TRANSMITTER			
RF Power Output	Mid Power	30 W to 1 W	30 W to 1 W 25 W to 1 W (490-520 MHz)
	High Power	50 W to 10 W	45 W to 10 W 40 W to 10 W (490-512 MHz) 35 W to 10 W (512-520 MHz)
Spurious Response		73 dB	75 dB
FM Hum & Noise	Analog @ 25 kHz Analog @ 12.5 kHz	50 dB 45 dB	50 dB 45 dB
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 14K4F1D, 11K0F3E, 8K30F1E 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Footnotes from front:

¹ Requires compatible PC software application or console.

² These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

³ Up to 8 different Trunked networks can be configured per radio (each in a zone)

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54: Radio itself IP54/55: Remote head				

KENWOOD

JVCKENWOOD USA Corporation

Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

www.kenwood.com/usa

JVCKENWOOD Canada Inc.

Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

www.kenwood.ca



ISO9001 Registered
JVCKENWOOD Corporation

ADS#08415 Printed in USA