

Introducing the new TK-D740/D840 mobiles, launched together with the new TK-D240/D340 portables and completing KENWOOD's impressive DMR system line-up. Thanks to compliance with MIL-STD and IP54 environmental standards, they can be relied on through thick and thin. As well as handling both analog and digital communications, these user-friendly DMR radios can even operate in direct mode, without a repeater. They also offer KENWOOD Call Interrupt and also benefit in having KENWOOD enhanced audio quality. These truly resourceful team members will enable you to make the most of your legacy analog equipment while also benefitting from digital communications.

### Two-slot TDMA

Belonging to the DMR Tier II category, which covers licensed conventional systems, these radios are specified for 2-slot Time Division Multiple Access (TDMA) operation in 12.5 kHz channels. This means they can offer greater spectrum efficiency.

### Two-in-One – Digital & Analog

These DMR radios can operate in both digital and FM analog modes, switching automatically as needed. Interoperability with legacy analog radios allows organizations to migrate to full digital at their own pace.

### Dual-slot Direct Mode

Up to two simultaneous direct-mode subscriber calls can be supported in a 12.5 kHz channel, without requiring a repeater, thus doubling channel capacity.

### Call Interruption

In an emergency or whenever a user needs to interrupt a call, Call Interrupt is available in both direct and repeater modes, while encoding or decoding. Also featured are emergency functions to help protect staff in remote areas, etc.

### Tough All-terrain

These TK-D740/D840 mobile radios conform to MIL-STD C/D/E/F/G standards for ruggedness, and are IP54 rated for water & dust intrusion, making them more than capable of withstanding harsh operating conditions.\*

\*Applies only when using a microphone KMC-35 or KMC-36.

### 2-Digit LED Channel Display with Brightness Control

The large 2-digit LED display provides a clear indication of which channel is being used, and the brightness level can be adjusted (high/low) to suit the time of day and ambient light conditions. The front panel also features 9 programmable function keys for enhanced operating ease.

### Programmable Blue LED

The blue LED indicator can be customized to provide useful status information. For example, it can be used in combination with the orange LED for Selective Call differentiation.

### Clear, Powerful Audio

A radio's most important quality is clarity – being able to hear, loud and clear, what the other party is saying, and these mobiles deliver just that. For instance, the AMBE+2™ VOCODER technology accurately replicates natural human speech nuances for superior voice quality, even with high levels of ambient noise. Additionally, Voice Announcement can confirm the channel number, so there is no need to look at the display. English is the default language, but Spanish and French are also available\*.

\*Availability varies depending on the region.

### Other features

- Max. 32 ch in 2 zones (16 ch per zone)
- Wide 70 MHz UHF coverage
- External D-sub 15-pin (DE-15) interface
- External speaker connector (3.5 mm diameter phone jack)
- Audio output power 4 W @ 4 Ω
- GPS connectivity (future firmware update)
- Single zone and Normal scanning functions
- Horn alert/P.A. function
- Ignition sensing
- Password protection (read/overwrite)
- Minimum volume setting
- Embedded message
- Selective call alert LED
- Late entry
- Analog signalling: QT/DQT, FleetSync, 2-tone (available later)
- Comander per channel
- Squelch level

#### TKR-D710/D810 VHF/UHF DIGITAL REPEATER



#### KTI-5 INTERFACE BOX



- DMR Tier II Compatible Air Interface
- DMR Digital Conventional & FM Analog Conventional modes
- 136-174 MHz, 50-5 W; 450-520 MHz, 40-5 W; 400-470 MHz, 40-5 W
- 30 Channel Capacity
- 6 Backlit Programmable Function Keys
- Two-digit LED Display
- Conventional IP Network\*
- AIS IP Console Interface\*

\*Requires Interface Box KTI-5 installed with the IP Network Software.

Note: The TKR-D710/D810 is not compatible with duplex/simplex base operation but only for repeater operation.



## OPTIONS



All accessories and options may not be available in all markets. Contact an authorized KENWOOD dealer for details and complete list of all accessories and options.

## SPECIFICATIONS

	TK-D740	TK-D840
<b>GENERAL</b>		
Frequency Range	136-174 MHz	400-470 MHz 450-520 MHz
Number of Channels	32 ch/2 zones (Max. 16 ch/zone)	
Channel Spacing	Analog	25/12.5 kHz
	Digital	12.5 kHz
Operating Voltage	13.6 V DC ±15 %	
Operating Temperature Range	-30°C to +60°C	
Frequency Stability	±2.0 ppm	±1.0 ppm
Antenna Impedance	50 Ω	
Dimensions (W x H x D)	160 x 43 x 122.6 mm	
Weight (net)	1.1 kg	
<b>RECEIVER</b>		
Sensitivity	Digital 1 % BER	0.45 μV
	Digital 5 % BER	0.3 μV
	Analog (12 dB SINAD) @ 25/12.5 kHz	0.25 μV
Adjacent Channel Selectivity	Analog @ 25/12.5 kHz	75/65 dB
Intermodulation Distortion	Analog	73 dB
Spurious Response	Analog	75 dB
Audio Distortion	Less than 5 %	
Audio Output	4 W/4 Ω	

	TK-D740	TK-D840
<b>TRANSMITTER</b>		
RF Power Output	High/Mid	50-5 W/25-5 W
Spurious Response		73 dB
FM Hum & Noise	Analog @ 25/12.5 kHz	45/40 dB
Audio Distortion	Less than 5 %	
Emission Designator	16K0F3E, 14K0F2D, 14K0F3E, 12K0F2D, 11K0F3E, 7K50F2D, 7K60FXE, 7K60FXD	

Specifications shown are typical.  
Analog measurements accord with TIA 603, EN 300 086 & 219.  
Digital measurements accord with EN 300 113.  
Details and timing of firmware and software updates are subject to change without notice.  
Specifications are subject to change without notice, due to advancements in technology.

FleetSync® is a registered trademark of JVCKENWOOD Corporation.  
AMBE+2™ is a trademark of Digital Voice Systems Inc.  
All other trademarks are the property of their respective holders.

## ENVIRONMENTAL SPECIFICATIONS

MIL-STD	Method / Procedures				
	810C	810D	810E	810F	810G
Low Pressure	500.1/I	500.2/I, II	500.3/I, II	500.4/I, II	500.5/I, II
High Temperature	501.1/I, II	501.2/I, II	501.3/I, II	501.4/I, II	501.5/I, II
Low Temperature	502.1/I	502.2/I, II	502.3/I, II	502.4/I, II	502.5/I, II
Temperature Shock	503.1/I	503.2/I	503.3/I	503.4/I, II	503.5/I
Solar Radiation	505.1/I	505.2/I	505.3/I	505.4/I	505.5/I
Rain*1	506.1/I, II	506.2/I, II	506.3/I, II	506.4/I, III	506.5/I, III
Humidity	507.1/I, II	507.2/II, III	507.3/II, III	507.4	507.5/II
Salt Fog*1	509.1/I	509.2/I	509.3/I	509.4	509.5
Dust*1	510.1/I	510.2/I	510.3/I	510.4/I, III	510.5/I
Vibration	514.2/VIII, X	514.3/I	514.4/I	514.5/I	514.6/I
Shock	516.2/I, II, III, V	516.3/I, IV, V	516.4/I, IV, V	516.5/I, IV, V	516.6/I, IV, V
<b>International Protection Standard</b>					
Dust & Water Protection	IP54*1				

\*1: Testing requirements are: (a) Microphone (KMC-35/36) is connected; (b) cap is installed on D-sub 15pin connector; (c) external antenna is connected to antenna receptacle; and (d) neither the KCT cable nor speaker cable is connected.

**JVCKENWOOD Corporation**  
Professional Systems Segment  
Communications Equipment Business Unit  
1-16-2 Hakusan, Midori-ku, Yokohama-shi, Kanagawa, 226-8525 Japan  
www.jvckenwood.co.jp/en

