

GENERAL FEATURES

- 136-154, 146-174 MHz
- 400-430, 450-480, 480-512 MHz
- 5 W Exciter Output
- 50 / 110 / 150 Watt VHF Systems
- 40 / 100 / 150 Watt UHF Systems
- Repeater Operation
- Duplex/Simplex Base Operation
- 30 CH Scanning Base (Conventional)
- Two-Digit LED Display
- LED Status Indicators
- 6 Programmable Function Keys
- 0.3 W Front Panel Speaker
- 3 W External Speaker Audio
- Volume Control
- Program/Modem Interface
- Remote Termination Interface
- Programmable AUX I/O's
- DTMF Front Panel PF Key Control
- DTMF AUX Output Control
- DTMF AUX Input Monitoring
- KPG-109D Windows® FPU
- Flash Firmware Upgrading

DIGITAL – GENERAL

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- UID & GID Validation
- NXR Over-the-Air Alias
- KXK-3 OCXO Option (6.25 kHz operation)
- NXDN® Scrambler Included
- Telephone Interconnect Option

DIGITAL – CONVENTIONAL MODE

- 16 RAN Repeater Controller Built-in
- 1,000 GIDs Per Site
- 1,000 UIDs Per Site
- Mixed FM/Digital Operation
- Conventional IP Networks
- Site Roaming Capability

DIGITAL TRUNKING OPTION

- 3,000 GIDs Per Site
- 3,000 UIDs Per Site
- 30 Channels Per Site
- Transmission Trunked Mode
- Message Trunked Mode
- Busy Call Queuing
- Call Queue Pre-emption
- Late Entry (UID & GID)
- Control Channel Rotation
- Control / Traffic Channel Switching
- Cross-Busy
- Fail Soft Mode
- NXDN® & LTR® Traffic Channel Sharing
- 2MB Call/Activity Memory
- Compact Flash Memory Expansion
- ESN Validation

MULTI-SITE IP NETWORK OPTION

- Upto 16/48 Site Configurations
- 65,519 GIDs Per Network
- 65,519 UIDs per Network
- NEXEDGE® Trunked Features
- Ethernet Network Interface
- IP LAN/WAN Connectivity
- Wide Area All Group Call
- Group Registration
- Auto-Roaming
- Registration & De-Registration
- Secure VPN Connections
- Use of Off-the-Shelf 10 Base-T/100 Base-TX Ethernet Switching & Routers

KPG-110SM SYSTEM MANAGER

- Trunked Sites & IP Network Systems Only
- Windows® 2000/XP/Vista®/7 Compatible
- USB Secure Key Access
- Direct, Dial-Up & IP Connectivity
- Subscriber Privileging
- 127 UID/GID Class Of Service Entries
- 5,000 Fleets (UID/GID User Lists)
- Group Call Inter-Site Limits
- Remote Site Programming
- Real-Time Activity Monitoring
- NXR/Network Interface Diagnostics
- Call Logging / Event Download
- Remote System Firmware Updates

ANALOG MODES – GENERAL

- 25 & 12.5 kHz Channels
- Encryption/ANI Board Control

ANALOG CONVENTIONAL MODE

- 16 QT/DQT Repeater Control Built-in
- Hang Timer / Time Out Timer / CW ID
- External FM Controller Interface

ANALOG LTR® TRUNKED MODE


- External LTR® Controller Interface
- External MPT Controller Interface



Options

KXK-3

OCXO Unit
(Required for
6.25 kHz operation)



KMC-9C

Desktop Microphone



KTI-4M

Telephone Interconnect
Adapter (Requires telephone patch)



KMC-35

Microphone



KES-5

External Speaker



Main Specifications

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

GENERAL		NXR-700	NXR-800
Frequency Range	K K2 K3	146-174 MHz 136-154 MHz	450-480 MHz 480-512 MHz (RX) / 477-512 MHz (TX) 400-430 MHz
Channel Spacing	Analog Digital	12.5 / 15 / 25 / 30 kHz 6.25 / 12.5 kHz	12.5 / 25 kHz 6.25 / 12.5 kHz
PLL Channel Step		2.5 / 3.125 / 5 / 6.25 kHz	3.125 / 5 / 6.25 kHz
Frequency Stability	With KXK-3 (for 6.25 kHz)		± 1.5 ppm ± 0.5 ppm
Operating Voltage			13.8 V DC ± 15%
Operating Temperature Range			-22° F to + 140° F (-30° C to +60° C)
Antenna Impedance			50 Ω
Dimensions (W x H x D) Projections not included			19.02 x 1.73 x 13.03 in (483 x 44 x 331 mm)
Weight (net)			11 lb (5 kg)
FCC ID	K K2 K3	K44371300 K44371301	K44371400 K44371401 K44371402
IC Certification	K K2 K3	282F-371300 282F-371301	282F-371400 282F-371402
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER) Digital @ 12.5kHz (3% BER) Analog (12 dB SINAD)		0.27 μV 0.33 μV 0.30 μV
Selectivity	Analog @ 25/30 kHz Analog @ 12.5 kHz	93 dB (± 30 kHz) 85 dB (± 12.5 kHz)	87 dB (± 25 kHz) 81 dB (± 12.5 kHz)
FM Hum & Noise	Analog @ 25/30 kHz Analog @ 12.5 kHz		60 dB 55 dB
Intermodulation Distortion			85 dB (± 50 / 100 kHz)
Spurious Response			100 dB
Audio Distortion (Ext. SP)			Less than 2% (at 0.3W)
Audio Output (Ext. SP)			3 W (at 4 Ω, less than 5% distortion)
TRANSMITTER			
RF Power Output			5 W to 0.5 W
Spurious & Harmonics			73 dB
FM Hum & Noise	Analog @ 25/30 kHz Analog @ 12.5 kHz		55 dB 50 dB
Audio Distortion			Less than 1% at 1000 Hz
Modulation			16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

Analog measurements made per TIA/EIA 603 and specifications shown are typical.
Specifications are subject to change without notice, due to advancements in technology.

Windows® and Windows Vista® are registered trademarks of Microsoft Corporation
LTR® is a registered trademark of Transcript International.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc.
NEXEDGE® is a registered trademark of JVCKENWOOD Corporation.

KENWOOD

JVCKENWOOD USA Corporation

Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

www.kenwood.com/usa

JVCKENWOOD Canada Inc.

Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8

www.kenwood.ca



ISO9001 Registered
JVCKENWOOD Corporation

ADSH10115 Printed in USA